



A product of Halo&Son AUSTRIA

Datasheet

Product ID: CoFlex1000-698-3800



The CoFlex1000-698-3800 LPDA Antenna by Halo&Son Austria is compatible with all 5G, LTE, UMTS and GSM network providers and frequencies* throughout Europe. Depending on the frequency band used, a considerable gain of 9dB to 10dB is achieved.

The plastic cover protects the directional antenna safely from snow and rain. So even with bad weather an outstanding connection.



4GLTE Compatible





2x2 MIMO Compatible







((

No matter whether your Internet is slow, or the connection fluctuates strongly or even fails. Halo&Son has the right solution for you with the CoFlex1000 directional antenna!

RoHS


IP55

The CoFlex1000 antenna is suitable as an outdoor antenna for 2G / 3G / 4G / 5G routers and repeaters. Hotels, businesses, restaurants, flats, houses, holiday homes, mountain huts, autarkic systems as well as in many other applications, the CoFlex1000 antenna from Halo&Son has greatly improved the Internet connection of our customers.





Temp. -40°C Range +60°C



✓ High Gain

- ✓ Wide Bandwidth
- ✓ Weatherproof Construction
- ✓ 2x2 MIMO Compatible
- ✓ Excellent performance
- ✓ Connection Distance up to 10km

Think about the environment!

We at Halo&Son try to save unnecessary resources, therefore you will not find printed instructions in this antenna set.

Instead you can simply scan this QR code with your smartphone camera and you will immediately get the manual in PDF format.

If you don't have a smartphone, that's not too bad. Just visit us at www.halo-son.com and you will find all data sheets, manuals and lots of helpful information.



Datasheet



User Manual

Electrical Specifications

Frequency Range*: 698-960MHz/1710-2700MHz

3400-3800MHz 9dB / 10dB / 10dB

Gain: 9dB / 10dB / 10 3 dB H Beamwidth: 65° / 60°/ 60° 3 dB V Beamwidth: 50° / 45° / 40°

Polarization: +45°/-45° (Cross-Polarized)

VSWR: \leq 1,5 Impedance: 50 Ohm Max. Power: 50W Front to Back Ratio: \leq 12 / \leq 15dB

Mechanical Specifications

Connector: N-Female

Mounting: Bracket with U-bolt for 25-50mm mast

Weight: 0,7kg Wind Velocity: 60m/s

Developed, designed and quality tested by Halo&Son in Austria. Assembled under highest quality standards in China.

Disclaimer: Please read the instruction manual before use. The Internet speed actually achieved depends on several factors. All images, text and graphics are Copyright protected and are provided only for viewing. All information is without Guarantee of completeness. The provided content is subject to change without Notice.

This is a product of **Halo&Son Austria** Lerchenstraße 17, 5023 Salzburg, AUSTRIA